



External locking rim dimensions 10~21 "
Internal locking rim dimensions 12~24 "
Max. Wheel diameter 1040mm(41 ")
Max. Wheel width 355mm(14 ")
Working Pressure 8-10bar
Power supply 110V (1ph)/ 220V (1ph)/ 380V (3ph)
Optional Motor power 0.75/0.55/1.1 kw
Max. Rotating Torque (Turntable) 1078 Nm
Overall Dimension 96*76*86cm
Noise Level 75 Db



200 mm

901-0026-19

152.6mm

ATP Automotive



External locking rim dimensions 10~21 "
Internal locking rim dimensions 12~24 "
Max. Wheel diameter 1040mm (41 ")
Max. Wheel width 355mm(14 ")
Working Pressure 8-10bar
Power supply 110V (1ph)/ 220V (1ph)/ 380V (3ph)
Optional Motor power 0.75/1.1 kw
Max. Rotating Torque (Turntable) 1078 N•m
Overall Dimension 960*760*860 mm
Noise Level <75dB



901-0027-19

152.6mm



TECHNICAL DATA

Hydraulic Pump motor 1.5KW

Rotating motor 2.2KW

Clamping capacity 14"-26"

Max. wheel diameter 1600mm(63")

Max. wheel width 780mm(30")

Max. wheel weight 500kg(1102lbs)

N/G Weight 520/670kg(1146/1477lbs)

Package dimension 2000*1580*970mm

Acoustic pressure level(at work) LPA<70dB(A)



901-0028-19

152.6mm

ATP Automotive



Hydraulic Pump motor 220v(3ph),3.0KW/380v(3ph),4.0kw

Rotating motor 220v(3ph),2.4KW/380v(3ph),3.0kw

Clamping capacity 14"-56"

Max. wheel diameter 2500mm(98")

Max. wheel width 1200mm(47")

Max. wheel weight 2200kg(4850lbs)

N/G Weight 960/1080kg(2116/23816lbs)

Package dimension 2320*2210*1000mm

Acoustic pressure level(at work) LPA<70dB(A)



901-0029-19

152.6mm



2.1 Specification

Max wheel weight: 65kg
Motor power: 200W
Power supply: 220V/50Hz
Balancing precision: $\pm 1g$
Rotating speed: 200r/min
Cycle time: 8s
Rim diameter: 10"~24"(256mm~610mm)
Rim width: 1.5"~20"(40mm~510mm)
Noise: <70dB
Net weight: 105kg
Dimensions: 960mm×760mm×1160mm



901-0030-19

152.6mm

ATP Automotive



Max wheel weight: 150kg/143lbs
Motor power: 750W/550W
Power supply: 222V(1/3PH)/380V(3PH)
Rotating speed: 200r/min
Cycle time: 8s
Rim diameter: 13" ~ 24" (330mm~610mm)
Rim width: 5.5" ~ 20" (140mm~510mm)
Noise: <70dB
Net weight: 226kg/498lbs
Dimensions 1220mm 960mm 210mm



901-0031-19

152.6mm



Machine type 4T
Machine weight 616kg
Lifting capacity 4000kg
Machine lift height 1910mm
Platform initial height 110mm
Machine height 2850mm
Machine width 3420mm
Machine lifting time ≤ 45 s
Machine descent time about 45s
Standard power supply 3/N/PE~380V, 50Hz, 10A
Whole machine power 2.2kw
Hydraulic oil 8L corresponds to wearable hydraulic oil
Working temperature 5-40°C
Working humidity 30-95%
Noisy < 70db
Storage temperature -25°C~55°C



902-0039-19

263.6 mm



Machine type Scissor lift
Drive Electrical hydraulic
Lifting capacity 3000kg
Machine lift height 960mm
Platform initial height 115mm
Platform length 1480mm
Platform width 480mm
Lifting time $\leq 35s$
Descent time $\leq 35s$
Whole machine length 2020mm
Whole machine width 1760mm
Power supply 3/N/PE~380V, 50Hz, 10A
Whole machine power 2.2kw
Hydraulic oil 6L corresponds to wearable hydraulic oil
Working temperature 5-40°C
Working humidity 30-95%
Noisy < 70db
Storage temperature -25°C~55°C



902-0040-19

152.6mm





904-0043-19

152.6mm